



## Audible and visual indicator units

### Providing remote indication of the status of the fire alarm system

## Product Overview

- A range of indicator units with either red or yellow indicators to provide audible and visual status of alarms, isolations or other functions associated with the fire alarm or other systems.
- These units are available with a keyswitch to silence the internal buzzer or a keyswitch to illuminate the indicator and buzzer and provide a volt free contact for ancillary control functions when the keyswitch is operated.
- All units mount to a UK style, single gang back box or can mount to standard surface or flush single gang mounting boxes.

## Features

- Available with red or yellow high brightness, flashing LED indicators
- Can be used for Fire alarm warning, activated by a sounder circuit or to indicate and initiate an active isolation
- Optional silence buzzer keyswitch
- Disable buzzer option via internal jumper link
- Optional keyswitch to perform isolation
- Terminations for incoming and outgoing wiring
- Fits onto standard, single gang UK back box for flush mounting (use M10FCLGT)
- Surface mounting box supplied

## Panels

Product Code	Description	Size (mm)
<b>K24100-M10</b>	Red Fire alarm indicator	97 x 97 x 48
<b>K24110-M10</b>	Red Fire alarm indicator with buzzer silence keyswitch	97 x 97 x 48
<b>K24200-M10</b>	Yellow alarm indicator	97 x 97 x 48
<b>K24210-M10</b>	Yellow alarm indicator with control keyswitch	97 x 97 x 48
<b>M10FCLGT</b>	Flush Mounting Collar (will fit single gang deep flush back box)	

## Technical

<b>Construction</b>	- 1.2mm mild sheet steel
<b>Finish</b>	- Epoxy powder coated
<b>Colour - lid &amp; box</b>	- BS 00 A 05 grey - fine texture
<b>Voltage</b>	- 18 to 30 V DC
<b>Power Consumption</b>	- 25 milliamps at 24V
<b>Operating temperature</b>	- -5°C to +50°C
<b>Operating humidity</b>	- To 95% non-condensing



Model No. K24110-M10



Model No. K24210-M10